

Products <sup>2</sup>		
Option	Voltage	XAR Round Area
G <sup>2</sup>	120-277	40-120 LEDs
	347/480	40-120 LEDs
K	120-277	40-60 LEDs
	347/480	n/a
DK	120-277	40-60 LEDs
	347/480	n/a
L	120-277	40-120 LEDs
	347/480	40-120 LEDs
CL	120-277	40-120 LEDs
	347/480	n/a
DL	120-277	40-60 LEDs
	347/480	n/a

1. See HL option drive current chart
2. Refer to the Multi-level spec sheet for additional options for the Round Area Light for DA, DL, and AA mounts.

Additional Options Available with Multi-Level		
Option	Voltage	XAR Round Area
G <sup>2</sup>	120/277	F
	347/480	N/A
K	120/277	F
	347/480	N/A
DK	120/277	F
	347/480	N/A
L	120/277	F
	347/480	F
CL	120/277	F
	347/480	N/A
DL	120/277	F
	347/480	N/A

F = Fuse

HL Option Drive Current Configurations		
Leads		Drive Current Output
175mA	350mA	
ON	OFF	175
OFF	ON	350
ON	ON	525

Multi-Level Options		
Option	Drive Current (mA)	Sensor Included
G	175/350/525	NO
K	175/525	YES
DK	350/700	YES
L	0/350	YES
CL	0/525	YES
DL	0/700	YES

Output Multipliers				
Drive Current (mA)	Lumen Multipliers	Power Multipliers	L70 Life Hours @ 25° C (77°F)	50K Hours Lumen Maintenance Level @15°C (59°F)
175	0.66	0.48	> 150K	95%
350	1.00	1.00	> 150K	94%
525	1.40	1.51	131K	93%
700	1.71	2.03	113K	91%

Note: Multipliers are for estimating purposes only. Check actual spec sheet data where available

